

Telehandler / Zoom Boom

Used Telehandler Nevada - Telehandlers go by many different names including a boom lift, telescopic handler, Cherry picker or teleporter. This industrial equipment is commonly used in a variety of industries including agriculture. This machine functions similarly to a crane and a forklift with the ability to extend upward and forward. The operator can utilize a variety of attachments at the end of the articulating boom to complete different jobs. Different attachments such as a bucket, pallet forks, a muck grab or a winch can help the machine complete many jobs. The main telehandler attachment is the pallet forks. Pallet forks enable the operator to move loads to and from a variety of locations that would otherwise be considered unreachable with a standard forklift. These machines enable cargo pallets to be unloaded and loaded from a trailer and placed on rooftops, racking or other high and hard to access locations. Often, high rooftop locations would need a crane although, telehandlers can accomplish these tasks much more efficiently. It isn't always practical or affordable to rely on a crane or secondary machinery to complete the job. A bucket grab or a bucket is the most common attachments for telehandlers within the agricultural sector.

Transporting items from unreachable places that cannot use a backhoe loader or a wheeled loader is one of the main advantages of using a telehandler. Telehandlers are beneficial for applications that would usually require a loading ramp or conveyor since they are capable of directly accessing trailers with high sides and hoppers. Having one item to complete a variety of jobs saves time, money and storage space. Telehandler machines can work in conjunction with a crane jib. Many attachments can be used such as power booms, grain and dirt buckets and rotators. The agricultural models can use three-point linkage and power take-off to make telehandlers multi-tasking. However, the main advantage of the telehandler is additionally its' largest limitation. When raising or extending with heavy loads, the boom functions similar to a lever. Despite significant counterweights in the rear, the telehandler can be subject to instability at times, decreasing the lifting capacity as the working radius or distance between the center of the load and the front of the wheels increases. When a telehandler functions as a single boom loader (as opposed to twin arms) and carrying a heavy load, there can be a potential for weakness even in the best designs. A machine with a 5K lb. capacity could safely lift 400 lbs. while fully extended using a retracted low boom angle. The same piece of equipment with a five thousand pound lift capacity and retracted boom may be capable as supporting up to ten thousand pounds once the boom is raised to seventy degrees. Monitoring the angle, weight and boom height, there are load charts on this equipment to outline which tasks can be safely conducted. Newer telehandler models rely on computers and sensors to monitor the machine. The operator cannot continue once the machine's limits have been reached. They are warned and cut off from accessing the control input. There are front stabilizers that can drastically enhance the machine's lifting capacity while it is stationary. Another option is a stabilizing rotary joint between lower and upper frames, often referred to as a mobile crane that can additionally utilize a bucket. Compact telehandler models are available in a variety of different weights, reach, sizes and boom designs. Telehandlers that weigh 11,000 pounds or less fall into the compact category. Compact models feature a two-stage boom design in comparison to the three or four boom design that is common with larger units. Compact models rely on a low pivot boom to facilitate better cab visibility as the operator transports loads. Obviously, the compact telehandler has narrower and tinier dimensions. The reach capacity for compact units is between thirteen to twenty feet and these units offer a lift capacity from five to seven thousand pounds. The versatility of the compact telehandler makes it popular in a variety of applications. Telehandlers can function as a pick and place unit or a tool carrier. It is commonly utilized in spaces that are tight and cramped. It is common for contractors to use this machine during framing and for residential jobs where there are height restrictions. These machines can facilitate internal building access. Compact telehandlers are used in many applications including nurseries, erecting steel, multi-story construction, masonry, strip malls, garages and similar jobs. Telehandlers are employed by

agri-business and farming applications to complete many jobs. Telehandlers are made with two or four-wheel drive as well as crab steering. This machine can traverse longer distances with two-wheel drive at higher speeds to facilitate easy travel between worksites. The 4-WD units are capable of having a tighter turning radius and can travel difficult terrain. Crab steering increases overall maneuvering and enables the front and back wheels to move 45 degrees to the left or the right. There are a variety of cab interior options available for compact telehandlers. On entry-level models, there is a rollover cage for added safety. Higher models come with a heater, a completely enclosed cab, defroster and windshield wiper. Compact units feature spacious cab accommodations to keep operators totally comfortable. Additional features such as cup holders, air conditioning, tilt steering, suspension seats and satellite radio are all options. The numerous attachment options are facilitated with high-pressure and high-flow auxiliary hydraulics. These attachments increase the functions the machine is capable of. Compact machines conduct ground-engaging jobs. It is easy to enjoy the benefits of a mini excavator by adding a simple bucket attachment to the telehandler. There are popular attachments including brooms for sweeping, truss booms for extended reach, side-shifting and rotating fork carriages, heavy and light-duty buckets, augers for planting trees or digging holes and many items. Skid steer attachments are being made for versatility and other compact telehandler designs.